




CardiMax FX-7202

Advanced Electrocardiograph

Features :

- Touch Screen for Easy Operation
- Alpha-numeric Keyboard
- 3/6/12 Lead ECG Display
- 3/6 channels on 110 mm paper
- Optional Interpretation Program
- Built-in Memory for ECG Storage
- Communication Port for External Storage
- Optional Battery Operation for Portability



FX-7202 Specifications

ECG

Leads	Standard 12 leads
Sensitivity selection	1/4, 1/2, 1, 2 cm/mV; manual or automatic
Time Constant	3.2 sec or greater
Frequency response	0.05 Hz to 150 Hz (within -3dB)
Common mode rejection ratio	103 dB or greater
Max. electrode potential	± 550mV or greater
A/D conversion	18 bits
Sampling frequency	8000 samples/sec/channel
Filters	AC: 50 or 60 Hz, -20dB or less Muscle: 25 or 35 Hz, -3dB (-6dB/oct) Drift: 0.25 or 0.5Hz, -3dB (-6dB/oct)

ECG Storage

Built-in memory	Up to 128 events
-----------------	------------------

Display

Device	Backlight LCD with Touch Screen
Display area	115 mm (H) x 86 mm (V)
Resolution	320 x 240 dots
Representation	3/6/12 channels ECG display

Operation

Devices for operation	Touch Screen and membrane keys (The touch screen is used for alphanumeric keyboard input)
-----------------------	--

Recorder

Method	Thermal dot array
Paper speed	10, 12.5, 25 or 50 mm/sec
Recording paper	Z-fold, 110mm x 20m, fold length:140mm (OP-222TE)

I/O interface

Communication port	RJ-45 connector
--------------------	-----------------

Safety

Regulatory standards	IEC60601-1, IEC60601-2-25
Electrical shock protection	Class I, Type CF and Internally powered equipment, Type CF
Conformity	CE marking per 93/42/EEC Directive

General

Power requirements	100 to 240V AC Universal, 50/60Hz, or 9.6V DC (optional rechargeable battery)
Dimensions	260 (W) x 206 (D) x 64 (H) mm
Weight	Approx. 2.5 Kg (w/o battery)

Option

Program cartridge	PC-7403: Interpretation
Rechargeable battery	T8HRAAU-4713 (Ni-MH)

FUKUDA DENSHI reserves the right to change specifications without notice.



FUKUDA DENSHI CO., LTD.

39-4, Hongo 3-chome, Bunkyo-ku, Tokyo 113-8483, Japan
Tel: +81-3-5684-1455 Fax: +81-3-3814-1222

Distributed by: